

Eksempel nr 19 - Permutering - alle (rekursive) funksjonskall ved tallarray lik "123"  
 Laget av Arnaud Duhamel (H22)

	<code>permutter(array, 0, 3)</code>	<code>permutter(array, 1, 3)</code>	<code>permutter(array, 2, 3)</code>
1	permutter(array, 1, 3) <b>123</b>		
2		permutter(array, 2, 3) <b>123</b>	
3			display(array) 123
4		bytt(arr[1], arr[2]) <b>132</b>	
5		permutter(array, 2, 3) <b>132</b>	
6			display(array) 132
7		roterVenstre(array, 1, 3) <b>123</b>	
8	bytt(arr[0], arr[1]) <b>213</b>		
9	permutter(array, 1, 3) <b>213</b>		
10		permutter(array, 2, 3) <b>213</b>	
11			display(array) 213
12		bytt(arr[1], arr[2]) <b>231</b>	
13		permutter(array, 2, 3) <b>231</b>	
14			display(array) 231
15		roterVenstre(array, 1, 3) <b>213</b>	
16	bytt(arr[0], arr[2]) <b>312</b>		
17	permutter(array, 1, 3) <b>312</b>		
18		permutter(array, 2, 3) <b>312</b>	
19			display(array) 312
20		bytt(arr[1], arr[2]) <b>321</b>	
21		permutter(array, 2, 3) <b>321</b>	
22			display(array) 321
23		roterVenstre(array, 1, 3) <b>312</b>	
24	roterVenstre(array, 0, 3) <b>123</b>		